

FHT/FHVB

Distribution Box

FHT /FHVB series distribution box use high-quality fire-resistant and ABS materials reach IP65 protection Degree the max current can be 125A. Can be used in outdoor environment to protect the heavy weather.



Flam mability rating: HB Flam mability rating: V-2

Specifications

Model No	Product Size(m m)	Product Weight(kg)
FHT-5WAY	120*160*95	0.34
FHT-8WAY	200*155*95	0.53
FHT-12WAY	250*195*110	0.84
FHT-15WAY	310*195*110	0.90
FHT-18WAY	365*195*110	1.07
FHT-24WAY	360*280*110	1.35
Model No	Product Size(m m)	
FHVB-4WAY	107*212*82	0.76
FHVB-9WAY	165*200*100	0.81
FHVB-12WAY	219*200*100	1.08
FHVB-15WAY	273*230*110	1.28
FHVB-18WAY	381*230*110	1.34
FHVB-24WAY	273*380*110	1.91
FHVB-36WAY	381*380*110	2.40

Solar Tools Kit

- 1 PCS A-2546B terminal crimping pliers (crimping range: 2.5-6mm² , included a locator)
- 1 PCS W X-0626 cable stripper (stripping range: 0.9-6mm²)
- One pair MC4 wrench, one pair MC4 connector
- MC3 and 30J head each pair



Main Speciality

- The new PV Crimping Pliers precision pressure line module locking (self locking and releasing mechanism) and the overall design;
- In the the repeated pressure line to maintain a higher standard of quality pressure line;
- The excellent lever transmission design, isobar larger cross-section of the wire, the m ore labor-saving;
- Ergonomic design;
- The positioning device can be fixed in the jaw , to ensure precise positioning of the terminal of the pressure line;
- Pressure line film and locator under the pressure line terminal selected.

Type	Capacity	AWG	Length	Weight
A-2546B(MC4)	2.5/4.0/6.0mm ²	14-10AWG	270mm	0.74kg
A-2546B-4(MC3)	2.5/4.0/6.0mm ²	14-10AWG	270mm	0.74kg
A-2546B-3	4.0/6.0mm ²	12-10AWG	270mm	0.74kg